

# SERKYD C27TX70

## PRODUCT TYPE

Short oil polyurethane glossy alkyd resin.

## SUGGESTED USES

Polyurethane lacquers and finishes, NC lacquers and especially non yellowing stoving enamels

## PROPERTIES

Excellent gloss and gloss retention

Excellent hardness and flexibility

Very high chemical resistance

Non yellowing

## COMPOSITION

Oil type : Coconut fatty acids

Oil content : %27

Solvent : Toluene/Xylene

## SPECIFICATIONS

NV (%) : 70 +1

Acid number : Max. 10

Colour, Gardner (%50) : Max. 2

Viscosity(25°C) Gardner : 40-55 sn.

OH Value (mg KOH/g solid) : 162.00

Density (gr./cm<sup>3</sup>) : 1,06

Appearance : Clear (visual observation)

## SOLUBILITY

Toluene

Xylene

Acetone

Butyl acetate

## PACKING

Resin is supplied in steel drum with net content 210kgs.

## STORAGE AND SHELF LIFE

The product should be stored indoors in the original unopened and undamaged packages in a dry place at storage temperatures between 5 °C and 30 °C. Exposure to direct sunlight should be avoided. The shelf life of the resin which under the mentioned storage conditions, is 12 months

